Brick installation

Style
Stepped Out 883

Fibre System
100% Solution Dyed Nylon

Pile Weight
18 oz/sq yard 610 g/m²

Gauge
1/12th inch

Density
5500

MaxxBac™
PVC free, 4 Layers:

1. Non-woven primary layer
   → *strong edges*
2. Advanced polymer pre-coat
   → *superior tuft lock*
3. Modified bitumen core
   → *stability in heavy traffic*
4. Polyester felt back
   → *reliable adhesion*

Format
Tile size: 19.7" x 19.7" 50 x 50 cm
Carton: 20 tiles = 6 sq yards = 5 m²

Installation Methods



Quarter-Turn Brick

Flammability
Critical Radiant Flux (kW/M²) 7.20
Smoke Developed (%.min) 93

ACCS Grading No: 17146
Contract Extra Heavy Duty including Stairs 4*
Residential Extra Heavy Duty including Stairs 6*

Air Quality Certified
Green Label Plus

Warranties
15 Year Wear Warranty
15 Year Stain Warranty

Performance
Specifications are based on averages from manufacturing processes and may vary within normal industry tolerance, including dye lots. Material supply and/or manufacturing process may require specification changes. Such variations do not affect product performance. This tile is manufactured for floorcovering use only. Chair pads are recommended under office chairs with roller castors to preserve appearance retention, avoid premature or accelerated wear and as a deterrent toward delamination. Entrance mats are recommended at building entry ways to reduce soiling. Due to dye lot variations, actual material may vary from sample. It is recommended that this tile be laid in accordance with AS2455. Professional cleaning is recommended.

Our goods come with guarantees that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for a major failure and compensation for any other reasonable foreseeable loss or damage. You are also entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality and the failure does not amount to a