

Luxury Vinyl Tile

Designer Outlet


INTERLOCKING

November 2025



INTERLOCKING

Gauge: 4mm ♦ Wear Layer: 0.3mm



3452 Grey Flagstone
298 x 602.8mm



3455 Classic Yorkstone
298 x 602.8mm



3427 Grey Mountain Ash
145.6 x 907.6mm



3431 Apple Tree
145.6 x 907.6mm



3438 Tan Limed Oak
177.4 x 1212.4mm



3462 Devonshire Oak
177.4 x 1212.4mm



3465 Dockyard Timber
177.4 x 1212.4mm



INTERLOCKING

Gauge: 4.5mm ♦ Wear Layer: 0.55mm



2857 Driftwood, Dark
145.6 x 907.6mm



2861 Limed Oak, Grey
177.4 x 1212.4mm



2862 Vintage Wood, Beige
177.4 x 1212.4mm



2873 Washed Pine Brown
177.4 x 1212.4mm





2874 Washed Pine Charcoal
177.4 x 1212.4mm



2881 Black Metalstone
298 x 602.8mm



2883 Original Concrete
298 x 602.8mm



2884 Industrial Concrete
298 x 602.8mm



Polyflor Vinyl LOC Underlay*

We recommend these interlocking products be installed by a flooring professional over **Polyflor Vinyl Loc Underlay**.

- Simple to use and easy to install
- Anti-slip surface
- Smooths out minor subfloor imperfections
- Acoustic benefits (19dB)

*Polyflor Vinyl LOC Underlay sold separately at an additional cost.



QUIET
UNDERFOOT



COMFORT
UNDERFOOT

Luxury Vinyl Tile

Designer Outlet

INTERLOCKING

November 2025



CHARACTERISTICS	STANDARD	4.0/0.3mm	4.5/0.55mm
Type of floor covering	ISO 10582 (EN 649)	Heterogeneous, PVC	Heterogeneous, PVC
Surface treatment		PUR	PU
Total weight	ISO 23997 (EN 430)	7025g/m ²	8600 g/m ²
Performance classification	ISO 10874 (EN 685)	23, 31	23, 33, 42
Gauge	ISO 24346 (EN 428)	4.0mm	4.5mm
Wear layer thickness	ISO 24340 (EN 429)	0.3mm	0.55mm
Dimensional stability	ISO 23999 (EN 434)	<0.10%*	≤0.15%*
Residual indentation	ISO 24343-1	<0.10mm*	<0.10mm*
Light fastness	ISO 105-B02 (Method 3)	≥6	≥6
Reaction to fire	EN 13501-1	Class Bfl-S1	Class Bfl-S1
Slip resistance**	DIN 51130 EN 13893	R10 Class DS	R10 Class DS
Static electrical propensity	EN 1815	≤2.0kV classified as 'antistatic'	≤2.0 kV classified as 'antistatic'
Castor chair (continuous use)	ISO 4918 (EN 425)	Suitable	Suitable
Underfloor heating		Suitable, max. 27°C	Suitable, max. 27°C
VOC emissions	AgBB/ABG	Very low emissions	Very low emissions
Plank Size		15 @ 145.6 x 907.6mm = 1.98m ² 9 @ 177.4 x 1212.4mm = 1.94m ²	15 @ 145.6 x 907.6mm = 1.98m ² 9 @ 177.4 x 1212.4mm = 1.94m ²
Tile Size		11 @ 298 x 602.8mm = 1.98m ²	18 @ 304.8mm x 609.6mm = 3.34m ²

* Average test value from current production.

** For clarification regarding slip, consult Polyflor technical services.

