## **2000** PUR

Attractive, high performance, heavy duty homogeneous sheet and tile floorcovering with a polyurethane reinforcement for low cost, lifetime polish free maintenance.

Featuring a directional duotone marbleised decoration, with marbleised highlight tones, 2000 PUR is available in a broad palette of vibrant shades. Demonstrating outstanding durability and abrasion resistance, 2000 PUR is recommended for use throughout commercial interiors, healthcare and education facilities, as well as retail outlets.



Gauge	EN 428/ISO 24346	2.0mm 2.5mm
Roll Size	EN 426/ISO 24341	2.0mm: 2m x 20m = 40m <sup>2</sup> 2.5mm: 2m x 15m = 30m <sup>2</sup>
Tile Size	EN 427/ISO 24342	2.0mm: 300mm x 300mm = 4.5m² 2.0mm: 608mm x 608mm = 5.17m² 2.5mm: 300mm x 300mm = 3.6m²
Total Weight	EN 430/ISO 23997	2.0mm: 3550g/m <sup>2</sup> 2.5mm: 4552g/m <sup>2</sup>
General Performance	EN 649/EN ISO 10581 ASTM F1913 ASTM F1700	Conforms Conforms Conforms
Use Area	EN 685/ISO 10874	
Reaction to Fire	EN 13501-1 ASTM E662* ASTM E648*	Class BfI-S1 <450 Class 1 *2.0mn
Abrasion Resistance	EN 660-2 EN ISO 10581	Group M Type II
Slip Resistance	EN 13893 AS/NZS 4586	Class DS R9
Indentation Residual	ASTM F970 (Modified)	Static load 750psi
Electrical behaviour (body voltage)	EN 1815	≤2kV Classified as 'antistatic'
Castor Chair (continuous use)	EN 425/ISO 4918	Suitable
Maritime Usage	American Bureau of Shipping* US Coast Guard Approved* Marine Equipment Directive 2014/90/EU* SOLAS 74*	Conforms Conforms Conforms Conforms *2.0mn
VOC Emissions	Indoor Air Comfort GOLD AgBB VOC test Floorscore Finnish M1 Classification* Swedish B.P.D (FLEC test)* GBCA/NZGBC Green Star IEQ-VOC	Eurofins certified product Pass Certified Pass Best Class Compliant *2.0mm
Responsible Sourcing	BES 6001	Very Good

Environmentally Preferable Flooring - Polyflor 2000 PUR achieves a BRE Global Environmental A+ Rating (Certificate No: ENP 472) in major use areas such as education and healthcare and is GreenTag LCA Rate certified with GreenRate level A - Gold Plus. Generic EN 15804 Environmental Product Declaration (EPD) available on request. Polyflor 2000 PUR is 100% recyclable and contains 25% recycled material. Recyclable via the Recofloor scheme. Visit www.polyflor.com/sustainability.

PUR - Polyflor 2000 PUR features a high quality, cross-linked polyurethane reinforcement, UV cured to provide a low-cost, polish free maintenance regime for the lifetime of the flooring.



Hygiene - All Polyflor commercial sheet vinyl ranges provide a continuous, impervious and hygienic flooring solution which can be confidently cleaned in accordance with recommended maintenance procedures and approved maintenance products. The implementation of an effective cleaning regime is the most important defence against infection.



Polyflor homogeneous PUR ranges are compatible for use with the most commonly used alco-based hand gels and are suitable for steam cleaning on a periodic basis. For information regarding handling and installation, adhesives, maintenance, applications, chemical resistance and product warranty, consult Polyflor Customer Technical Services on +44 (0)161 767 1912, or email tech@polyflor.com.

The data presented is correct at the time of printing. For latest information, please visit our website polyflor.com. Decoration and shade may vary slightly from the samples shown.





























